

§ 95.645

MHz and 1429–1432 MHz bands, the maximum field strength is 740 mV/m, measured at 3 meters.

[53 FR 36789, Sept. 22, 1988; 53 FR 44144, Nov. 1, 1988. Redesignated and amended at 61 FR 28769, 28770, June 6, 1996, and further redesignated and amended at 61 FR 46567, 46569, Sept. 4, 1996; 64 FR 69932, Dec. 15, 1999; 65 FR 44008, July 17, 2000; 65 FR 53190, Sept. 1, 2000]

EFFECTIVE DATE NOTE: At 65 FR 44008, July 17, 2000, and corrected at 65 FR 53190, Sept. 1, 2000, in § 95.639, paragraph (g) was added, effective Oct. 16, 2000.

CERTIFICATION REQUIREMENTS

§ 95.645 Control accessibility.

(a) No control, switch or other type of adjustment which, when manipulated, can result in a violation of the rules shall be accessible from the transmitter operating panel or from exterior of the transmitter enclosure.

(b) An R/C transmitter which incorporates plug-in frequency determining modules which are changed by the user must be certificated with the modules. Each module must contain all of the frequency determining circuitry including the oscillator. Plug-in crystals are not considered modules and must not be accessible to the user.

[53 FR 36789, Sept. 22, 1988. Redesignated at 61 FR 28769, June 6, 1996, and further redesignated at 61 FR 46567, Sept. 4, 1996; 63 FR 36610, July 7, 1998]

§ 95.647 FRS unit and R/C transmitter antennas.

The antenna of each FRS unit, and the antenna of each R/C station transmitting in the 72–76 MHz band, must be an integral part of the transmitter. The antenna must have no gain (as compared to a half-wave dipole) and must be vertically polarized.

[61 FR 28770, June 6, 1996. Redesignated at 61 FR 46567, Sept. 4, 1996]

§ 95.649 Power capability.

No CB, R/C, LPRS, FRS, MICS or WMTS unit shall incorporate provisions for increasing its transmitter power to any level in excess of the limits specified in § 95.639.

[65 FR 44008, July 17, 2000]

EFFECTIVE DATE NOTE: At 65 FR 44008, July 17, 2000, § 95.649 was revised, effective Oct. 16,

47 CFR Ch. I (10–1–00 Edition)

2000. For the convenience of the reader the superseded text is set forth below:

§ 95.649 Power capability.

No FRS, R/C, CB, LPRS, or MICS transmitter shall incorporate provisions for increasing its transmitter power to any level in excess of the limits specified in § 95.639.

[64 FR 69932, Dec. 15, 1999]

§ 95.651 Crystal control required.

All transmitters used in the Personal Radio Services must be crystal controlled, except an R/C station that transmits in the 26–27 MHz frequency band, a FRS unit, a LPRS unit, a MICS transmitter, or a WMTS unit.

[65 FR 44008, July 17, 2000]

EFFECTIVE DATE NOTE: At 65 FR 44008, July 17, 2000, § 95.651 was revised, effective Oct. 16, 2000. For the convenience of the reader, the superseded text is set forth as follows:

§ 95.651 Crystal control required.

All transmitters used in the Personal Radio Services must be crystal controlled, except an R/C station that transmits in the 26–27 MHz frequency band, a FRS unit, a LPRS unit, or a MICS transmitter.

[64 FR 69932, Dec. 15, 1999]

§ 95.653 Instructions and warnings.

(a) A user's instruction manual must be supplied with each transmitter marketed, and one copy (a draft or preliminary copy is acceptable provided a final copy is provided when completed) must be forwarded to the FCC with each request for certification.

(b) The instruction manual must contain all information necessary for the proper installation and operation of the transmitter including:

(1) Instructions concerning all controls, adjustments and switches that may be operated or adjusted without resulting in a violation of the rules.

(2) Warnings concerning any adjustment that could result in a violation of the rules or that is recommended to be performed by or under the immediate supervision and responsibility of a person certified as technically qualified to perform transmitter maintenance and repair duties in the private land mobile services and fixed services by an organization or committee representative of users of those services.